### MATERIAL SAFETY DATA SHEET – Smart Steel Epoxy Putty

### SECTION I: PRODUCT IDENTITY/MANUFACTURER

PRODUCT NAME: Smart Steel Putty Two-In-One Epoxy Putty

DATE PREPARED: January 2019

DISTRIBUTOR/MANUFACTURER: SMART PIPE WRAP SOLUTIONS

TELEPHONE NUMBER FOR INFORMATION: 0411 249 149 MAIL ADDRESS: P.O. Box 1859, New Farm QLD 4005

## SECTION II: HAZARDOUS INGREDIENTS/IDENTITY INFORMATION

HAZARDOUS COMONENTS APPROX. % OSHA PEL ACGIH TLV RECOMMENDED

2, 4, 6 – Tri (methyl aminomethyl) - - -

phenol (CAS 90-72-2)

19.8g/kg

Mercaptan Terminated Polymer - - LD50 (Dermal Rabbit)

(CAS unknown) >10.2 g/kg

SPECIAL HAZARD DESIGNATIONS

DOT (49CFR172): N/A

HMIS NFPA

OSHA (29 CFR 1910.1200) EVALUATION: HAZARDOUS

RCRA (40 CFR 261) EVALUATION: NON-HAZARDOUS Health: 2 2 EPA/TSCA Listed Ingredients: Yes Flammability: 0 0 SARA Listed Ingredients: None Reactivity: 0 0

BPA Epoxy Resign CAS – 25068-38-6 HAZARD SYMBOL – Xi RISK PHRASE – R36/38-43

Contains reaction product of Epichlorohydrin Bisphenol. A epoxide resign of average molecular weight >700 (10%-20%)

#### Classified Hazardous according to criteria of NOHSC

#### **Hazard Category - Irritant**

Risk Phases – R36/38 Irritant to eyes and skin; R43 May cause sensitization by contact by skin; S37/39 Wear suitable protective clothing, gloves, face and eye protection; S28 Wash hands and any other skin parts in contact with soap and water; S2 Keep out of the reach of children

KEY: 0 - Minimal 1- Slight 2 - Moderate 3 - Emrious 4- Severe

### SECTION III: PHYSICAL/CHEMICAL CHARACTERISTICS

BOILING POINT: N/D
SPECIFIC GRAVITY (H2O = 1): 1.9
VAPOR PRESSURE (MM HG.): N/D
MELTING POINT: N/D
VAPOR DENSITY (AIR = 1): N/D
EVAPORATION RATE (ETHYL ACETATE = 1): N/D
SOLUBILITY IN WATER: Negligible

APPEARANCE AND ODOR: Grey or White Semi-Solid / Slight Mercaptan Odor

#### SECTION IV: FIRE AND EXPLOSION HAZARD DATA

FLASH POINT (METHOD USED): N/A
FLAMMABLE LIMITS-LEL: N/A
UEL: N/A

EXTINGUISHING MEDIA: H2O spray, foam, CO2, dry chemicals SPECIAL FIRE FIGHTING PROCEDURES: Wear SCBA and protective clothing UNUSUAL FIRE AND EXPLOSION HAZARDS: May generate toxic or irritating fumes

### SECTION V: REACTIVITY DATA

STABILITY: Stable CONDITIONS TO AVOID: None

INCOMPATIBILITY (MATERIALS TO AVOID): Oxidizers

HAZARDOUS DECOMPOSITION: Aldehydes, Acids, CO, Sulfur Oxides

HAZARDOUS POLYMERIZATION: None.

## MATERIAL SAFETY DATA SHEET – Smart Steel Epoxy Putty

### SECTION VI: HEALTH HAZARD DATA

ROUTE(S) OF ENTRY:

INHALATION: N/A SKIN: Yes INGESTION: Yes

HEALTH HAZARDS (ACUTE AND CHRONIC): Prolonged skin or eye exposure may cause irritation

sensitization.

CARCINOGENICITY:

NTP: No IARC MONOGRAPHS: No OSHA REGULATED: No

SIGNS AND SYMPTOMS OF EXPOSURE:

EYES: Severe irritation. SKIN: Severe irritation.

INHALATION: N/A INGESTION: Nausea

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: N/A

**EMERGENCY AND FIRST AID PROCEDURES:** 

EYES: Flush with large amounts of water for 15 minutes. Seek medical attention SKIN: Wash with soap and water. If irritation persists, seek medical attention

INHALATION: N/A

INGESTION: Give large amounts of water. Induce vomiting. If unconscious, do not give

anything by mouth or induce vomiting. Seek medical attention.

# SECTION VII: PRECAUTIONS FOR SAFE HANDLING AND USE

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

Pick up spilled paste to prevent disposal in sewers,

waterways or soil.

Wear polyethylene gloves.

WASTE DISPOSAL METHOD: Collect and dispose of as non-hazardous in accordance

with all local, state, and federal regulations.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING:

Keep container closed when not in use.

Do not store near heat, sparks or open flame.

OTHER PRECAUTIONS: Keep out of reach of children.

## SECTION VIII: CONTROL MEASURES

RESPIRATORY PROTECTION

(SPECIFY TYPE): None

VENTILATION:

LOCAL EXHAUST: Acceptable

SPECIAL: N/A MECHANICAL (GENERAL): N/A OTHER: N/A

Polyethylene Safety Glasses PROTECTIVE GLOVES: **EYE PROTECTION:** 

OTHER PROTECTIVE CLOTHING

OR EQUIPMENT:

N/A WORK/HYGIENIC PRACTICES: Wash thoroughly before eating, drinking, smoking, or

leaving work area.